

View Online at <https://aerobasegroup.com/nsn/5320-01-533-1112>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.999 inches

Head Style:

Straight pan

Head Height:

Between 0.055 inches and 0.060 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3060 inches and 0.3220 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.687 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Special Features:

Furnished with collar

Material:

Stainless steel

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.