NSN 5320-01-533-7876

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-533-7876

Fastener Length:
Between 0.428 inches and 0.448 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.1597 inches
Head Minor Diameter:
Between 0.134 inches and 0.144 inches
Countersink Height:
0.0286 inches
Shear Strength:
32000 single pounds per square inch
Countersink Angle:
Between 99.5 degrees and 100.5 degrees
Heat Treatment:
T-81 solution heat treated
Material:
Aluminum alloy 2219
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize or chromate
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-a-8625 spec.