# NSN 5320-01-535-6140

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-535-6140



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.695 inches and 0.715 inches

### Head Style:

Belt

#### Width Between Flats:

Between 0.079 inches and 0.080 inches

#### Shank Diameter:

0.189 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.302 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

F15e lh/rh av

#### Grip Length:

0.380 inches

# Thready Qty Per Inch (tpi):

32

#### Thread Size:

0.190 inches

# Shear Strength:

125000 single pounds per square inch

# Countersink Angle:

100.0 degrees

#### Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-535-6140

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

