# NSN 5320-01-535-6346

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-535-6346



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 1.348 inches and 1.368 inches

### Head Style:

Straight pan

#### **Head Height:**

Between 0.120 inches and 0.135 inches

#### Width Between Flats:

Between 0.197 inches and 0.217 inches

#### Shank Diameter:

Between 0.373 inches and 0.375 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

#### Lubrication:

Cetyl alcohol

#### **End Application:**

C-17a aircraft

# Grip Length:

Between 0.808 inches and 0.818 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Material:

Steel comp 8740 or steel comp 4140

#### **Material Specification:**

Mil-s-6049 military specification single material response

#### **Surface Treatment:**

Cadmium

#### Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

---

# NSN 5320-01-535-6346

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

