NSN 5320-01-535-7079

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 1.050 inches and 1.070 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-535-7079

Head Style:						
Straight pan						
Head Height:						
Between 0.103 inches and 0.115 inches						
Width Between Flats:						
Between 0.220 inches and 0.224 inches						
Shank Diameter:						
0.499 inches						
Shank Style:						
Pin-rivet, straight, threaded						
Head Major Diameter:						
Between 0.735 inches and 0.770 inches						
Lubrication:						
Solid film and cetyl alcohol, specification 305, hi-shear corp						
End Application:						
F15e lh/rh av						
Grip Length:						
0.380 inches						
Thready Qty Per Inch (tpi):						
20						
Thread Size:						
0.500 inches						
Shear Strength:						
125000 single pounds per square inch						
Special Features:						
White paint on head						
Material:						
Steel comp xm-13						
Material Specification:						
Ams 5629 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response						
Thread Series Designator:						
Unjf						

NSN 5320-01-535-7079

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0