NSN 5320-01-535-7079

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-535-7079



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.050 inches and 1.070 inches

Head Style:

Straight pan

Head Height:

Between 0.103 inches and 0.115 inches

Width Between Flats:

Between 0.220 inches and 0.224 inches

Shank Diameter:

0.499 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

End Application:

F15e lh/rh av

Grip Length:

0.380 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Shear Strength:

125000 single pounds per square inch

Special Features:

White paint on head

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-535-7079

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

