## NSN 5320-01-537-6145

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-537-6145 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.502 inches and 0.522 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** 0.204 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol **End Application:** C-135 ccab **Grip Length:** 0.192 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5320-01-537-6145

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0