

View Online at <https://aerobasegroup.com/nsn/5320-01-537-6484>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.750 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.064 inches and 0.074 inches

**Width Between Flats:**

Between 0.079 inches and 0.081 inches

**Shank Diameter:**

0.205 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.357 inches and 0.377 inches

**End Application:**

C-135 ccab

**Grip Length:**

0.437 inches

**Thread Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.190 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

50.0 degrees

**Special Features:**

Shank diameter .0156 oversize

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

294, fscm 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0