

View Online at <https://aerobasegroup.com/nsn/5320-01-537-6484>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.750 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.079 inches and 0.081 inches

Shank Diameter:

0.205 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.357 inches and 0.377 inches

End Application:

C-135 ccab

Grip Length:

0.437 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

50.0 degrees

Special Features:

Shank diameter .0156 oversize

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

294, fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0