# NSN 5320-01-538-2198

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-538-2198



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.599 inches and 1.624 inches

### Head Style:

Flush countersunk

### Shank Diameter:

0.3403 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.501 inches and 0.554 inches

#### **Tip Diameter:**

0.3232 inches

## Lubrication:

Cetyl alcohol and dry film

### Grip Length:

Between 1.115 inches and 1.130 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.3125 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-538-2198

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

