## NSN 5320-01-538-2250

Pin-rivet - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-538-2250

Thread Direction:
Right-hand
Fastener Length:
Between 0.885 inches and 0.905 inches
Head Style:
Countersunk w/reverse chamfer
Head Height:
Between 0.1060 inches and 0.1230 inches
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.5018 inches and 0.5066 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.505 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28
28
28 Min. Tensile Strength (psi):
28  Min. Tensile Strength (psi): 6650 pounds per square inch
28  Min. Tensile Strength (psi): 6650 pounds per square inch  Thread Size:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Min. Tensile Strength (psi): 6650 pounds per square inch Thread Size: 0.250 inches Countersink Angle: 100.0 degrees Special Features: Injection hole 0.120 in. Lg located 0.240 in. From top of head Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response

## NSN 5320-01-538-2250

Pin-rivet - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0