

View Online at <https://aerobasegroup.com/nsn/5320-01-538-2787>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.067 inches and 1.087 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.1060 inches and 0.1230 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.5018 inches and 0.5066 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

0.687 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

6650 pounds per square inch

**Thread Size:**

0.250 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

Injection hole 0.120 in. Lg located 0.250 in. From top of head

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0