
# NSN 5320-01-539-1744

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.788 inches and 0.808 inches

## Head Style:

Straight pan

#### **Head Height:**

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.104 inches and 0.119 inches

#### Shank Diameter:

Between 0.202 inches and 0.203 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.357 inches and 0.377 inches

#### Lubrication:

Cetyl alcohol

#### **End Application:**

C-17a aircraft

## Grip Length:

Between 0.433 inches and 0.443 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 assn standard single material response or ams5737 assn standard single material response

#### Surface Treatment:

Passivate

#### **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-539-1744

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

