NSN 5320-01-539-3415

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-539-3415

Thread Class: За **Thread Direction:** Right-hand Fastener Length: Between 0.753 inches and 0.773 inches **Head Style:** Flush countersunk **Head Height:** Between 0.010 inches and 0.015 inches Width Between Flats: Between 0.104 inches and 0.119 inches **Shank Diameter:** Between 0.202 inches and 0.203 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.349 inches and 0.354 inches Lubrication: Cetyl alcohol **End Application:** C-17a aircraft **Grip Length:** Between 0.433 inches and 0.443 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Per hi-shear specification no 294 mfr ref single treatment response **Thread Series Designator:**

Unjf

NSN 5320-01-539-3415

Pin-rivet - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0