## NSN 5320-01-539-4368

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5320-01-539-4368

Right-hand
Fastener Length:
Between 1.365 inches and 1.385 inches
Head Style:
Flush countersunk
Head Height:
Between 0.010 inches and 0.015 inches
Width Between Flats:
Between 0.160 inches and 0.180 inches
Shank Diameter:
Between 0.3115 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.557 inches and 0.562 inches
Lubrication:
Cetyl alcohol
End Application:
C-17a aircraft
Grip Length:
Between 0.870 inches and 0.880 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.3125 inches
Countersink Angle:
100.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Per hi-shear specification 294 mfr ref single treatment response
Thread Series Designator:
Unjf

## NSN 5320-01-539-4368

Pin-rivet - Page 2 of 2



he			

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0