NSN 5320-01-539-4445

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-539-4445 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Green **Fastener Length:** Between 0.6525 inches and 0.6725 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Head Major Diameter:** Between 0.358 inches and 0.365 inches **End Application:** F18 aircraft **Grip Length:** Between 0.3075 inches and 0.3175 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.2500 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Pin, rivet, t-splin; pin, rivet, fluted threads-shear, 100 degree c'sunk, hexpoint drive **Special Features:** Cetyl alcohol used for lubricant on fastner head and shank only; green dye or paint used on chamfer face of threaded end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-539-4445

Pin-rivet - Page 2 of 2



Fiig:

A528u0