
NSN 5320-01-539-4445

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Green

Fastener Length:

Between 0.6525 inches and 0.6725 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Head Major Diameter:

Between 0.358 inches and 0.365 inches

End Application:

F18 aircraft

Grip Length:

Between 0.3075 inches and 0.3175 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.2500 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Criticality Code Justification:

Agav

Product Name:

Pin, rivet, t-splin; pin, rivet, fluted threads-shear, 100 degree c'sunk, hexpoint drive

Special Features:

Cetyl alcohol used for lubricant on fastner head and shank only; green dye or paint used on chamfer face of threaded end

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-539-4445

Pin-rivet - Page 2 of 2

Fiig: A528u0

