NSN 5320-01-539-7791

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-539-7791

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Green

Head Style:

Flush countersunk

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.3256 inches and 0.3304 inches

Tip Diameter:

Between 0.1570 inches and 0.1595 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Shear Strength:

1760 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Grip lg 0.6875 in.; lg 1.000 in.

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a



NSN 5320-01-539-7791

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.

