NSN 5320-01-539-9759

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-539-9759



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.185 inches and 1.205 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.094 inches and 0.096 inches

Shank Diameter:

Between 0.248 inches and 0.249 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

End Application:

CI-215 fire fighter aircraft

Grip Length:

Between 0.870 inches and 0.880 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

9300 double pounds per square inch

Countersink Angle:

45.0 degrees

Special Features:

Second dash number indicates grip in 1/16 ths

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard 1st material response or ams4967 assn standard 2nd material response

Surface Treatment:

Aluminum

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-539-9759

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

