# NSN 5320-01-540-0227

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.635 inches and 1.655 inches

### Head Style:

Straight pan

#### **Head Height:**

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.122 inches and 0.142 inches

#### Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.415 inches and 0.440 inches

#### Lubrication:

Cetyl alcohol

# End Application:

C-17a aircraft

# Grip Length:

Between 1.245 inches and 1.255 inches

#### Thready Qty Per Inch (tpi):

28

#### **Thread Size:**

0.250 inches

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams4967 assn standard single material response

#### Surface Treatment:

Aluminum

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-540-0227

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

