

View Online at <https://aerobasegroup.com/nsn/5320-01-540-2720>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.212 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.100 inches and 0.110 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.812 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

201000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

117000 single pounds per square inch

**Countersink Angle:**

45.0 degrees

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Spec, 258, caged73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0