## NSN 5320-01-540-5936

Pin-rivet - Page 1 of 2

**Thread Class:** 

**Right-hand** 

**Thread Direction:** 

Fastener Length:

Between 1.503 inches and 1.523 inches

3a

View Online at https://aerobasegroup.com/nsn/5320-01-540-5936



## Head Style: Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Shank Diameter: Between 0.357 inches and 0.377 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.1890 inches and 0.1895 inches Lubrication: Cetyl alcohol **End Application:** C-17a acft Grip Length: 1.188 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Product Name:** Pin-rivet, threaded **Special Features:** Head indented; centered point 0.05 min 0.06 maximum dia; 0.01 min 0.03 maximum depth Material: Titanium alloy **Material Specification:** Ams4967 assn standard single material response Surface Treatment: Aluminum **Surface Treatment Specification:** Dps 4.50-197 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

## Shelf Life:

N/a

## NSN 5320-01-540-5936

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

