# NSN 5320-01-541-0709

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-541-0709

## Head Style:

Straight pan

### Head Height:

Between 0.037 inches and 0.047 inches

#### Shank Diameter:

Between 0.168 inches and 0.169 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

#### Tip Diameter:

Between 0.157 inches and 0.159 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Shear Strength:

95000 single pounds per square inch

#### **Product Name:**

Hi-lok hi-tigue pin, protruding shear head alloy steel

#### **Special Features:**

Material specs per mil-s-5000 or mil-s-5626 or mil-s-6049

#### Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

#### Shelf Life:

N/a

#### Unit Of Measure:

```
---
```

## Demilitarization:

No

#### Fiig:

A528u0