NSN 5320-01-542-1579

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-542-1579 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.785 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2417 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.359 inches Tip Diameter: 0.2302 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.428 inches and 0.443 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 110000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-542-1579

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0