

View Online at <https://aerobasegroup.com/nsn/5320-01-542-3220>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.693 inches and 1.719 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

Between 0.451 inches and 0.473 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.640 inches and 0.711 inches

**Tip Diameter:**

Between 0.429 inches and 0.436 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

B-52

**Grip Length:**

Between 1.240 inches and 1.255 inches

**Thread Qty Per Inch (tpi):**

20

**Thread Size:**

0.438 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Bolt

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0