NSN 5320-01-542-3620

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-542-3620 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.225 inches and 2.250 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.508 inches and 0.540 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.731 inches and 0.803 inches **Tip Diameter:** Between 0.492 inches and 0.498 inches Lubrication: Cetyl alcohol **End Application:** B-52 **Grip Length:** Between 1.740 inches and 1.755 inches **Thread Size:** 0.500 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-542-3620

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0