# NSN 5320-01-542-3620

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-542-3620



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.225 inches and 2.250 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.508 inches and 0.540 inches

## Shank Style:

Pin-rivet, tapered, threaded

### Head Major Diameter:

Between 0.731 inches and 0.803 inches

### Tip Diameter:

Between 0.492 inches and 0.498 inches

### Lubrication:

Cetyl alcohol

# End Application:

B-52

## Grip Length:

Between 1.740 inches and 1.755 inches

## Thread Size:

0.500 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Bolt

#### Material:

Iron alloy 660

## **Material Specification:**

Ams 5737 assn standard single material response

#### **Surface Treatment:**

Cadmium

## Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-542-3620

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

