

View Online at <https://aerobasegroup.com/nsn/5320-01-542-3938>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.615 inches and 2.640 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.165 inches and 0.177 inches

**Shank Diameter:**

Between 0.435 inches and 0.469 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.720 inches and 0.734 inches

**Tip Diameter:**

Between 0.368 inches and 0.373 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

B-52

**Grip Length:**

Between 2.052 inches and 2.067 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Product Name:**

Bolt, taper shank, protruding head

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, cl 2 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0