
## NSN 5320-01-542-4247

Pin-rivet - Page 1 of 2





### Thread Class: 3a Thread Direction: Right-hand Fastener Length: Between 3.396 inches and 3.421 inches Head Style:

Straight pan

#### **Head Height:**

Between 0.165 inches and 0.177 inches

#### Shank Diameter:

Between 0.469 inches and 0.475 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.720 inches and 0.734 inches

#### **Tip Diameter:**

Between 0.368 inches and 0.373 inches

#### Lubrication:

Cetyl alcohol

#### End Application:

B-52

#### Grip Length:

Between 2.240 inches and 2.255 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Product Name:

Bolt, taper shank, protruding head

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, type ii, cl 2 federal standard single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-542-4247

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

