

View Online at <https://aerobasegroup.com/nsn/5320-01-542-4292>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.865 inches and 2.890 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.206 inches and 0.218 inches

**Shank Diameter:**

Between 0.503 inches and 0.547 inches

**Shank Style:**

Pin-rivet, tapered, threaded

**Head Major Diameter:**

Between 0.850 inches and 0.866 inches

**Tip Diameter:**

Between 0.429 inches and 0.436 inches

**Lubrication:**

Oil, sperm whale, specification 606, huck mfg co

**End Application:**

B-52

**Grip Length:**

Between 2.240 inches and 2.255 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.437 inches

**Product Name:**

Bolt, taper shank, protruding head

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, cl 2 federal standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0