## NSN 5320-01-542-4702

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-542-4702



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 2.350 inches and 2.375 inches

#### Head Style:

Straight pan

#### **Head Height:**

Between 0.141 inches and 0.153 inches

#### Shank Diameter:

Between 0.361 inches and 0.399 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.607 inches and 0.619 inches

#### **Tip Diameter:**

Between 0.305 inches and 0.310 inches

#### Lubrication:

Cetyl alcohol

#### End Application:

B-52

#### Grip Length:

Between 1.865 inches and 1.880 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.312 inches

#### **Product Name:**

Bolt, taper shank, protruding head

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type ii, cl 2 federal standard single treatment response

#### Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-542-4702

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

