

View Online at <https://aerobasegroup.com/nsn/5320-01-542-5387>

**Fastener Length:**

2.062 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.168 inches and 0.259 inches

**Width Between Flats:**

0.259 inches

**Shank Diameter:**

Between 0.514 inches and 0.515 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.717 inches and 0.752 inches

**End Application:**

A-10 acft

**Grip Length:**

Between 2.052 inches and 2.072 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Shear Strength:**

39600 double pounds per square inch

**Special Features:**

Cetyl alcohol lube per hi-shear specification 305

**Material:**

Steel comp 4340 or steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-6000 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6000 spec.