NSN 5320-01-542-9674

Blind Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-542-9674

| View Online at https://aerobasegroup.com/nsn/5320-01-542-9674 |
|--|
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.258 inches and 0.260 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| Between 0.499 inches and 0.507 inches |
| Expansion Device: |
| Threaded stem |
| End Application: |
| F/a-18 hornet |
| Grip Length: |
| Between 0.845 inches and 0.906 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, |
| lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. |
| Material: |
| Titanium alloy uns r56400 nut |
| Surface Treatment: |
| Passivate sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |