NSN 5320-01-542-9683

Blind Rivet - Page 1 of 1



lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	View Online at https://aerobasegroup.com/nsn/5320-01-542-9683
Shank Diameter: Between 0.258 inches and 0.260 inches Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Head Style:
Between 0.258 inches and 0.260 inches Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: Fra-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 9.9.0 degrees and 10.10 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Style: Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 9.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Shank Diameter:
Threaded self-plugging shank w/sleeve Head Major Diameter: Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 9.9.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.258 inches and 0.260 inches
Head Major Diameter: Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-I-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Shank Style:
Between 0.499 inches and 0.507 inches Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-I-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Threaded self-plugging shank w/sleeve
Expansion Device: Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Head Major Diameter:
Threaded stem End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.499 inches and 0.507 inches
End Application: F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Expansion Device:
F/a-18 hornet Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Threaded stem
Grip Length: Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	End Application:
Between 0.970 inches and 1.031 inches Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-I-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	F/a-18 hornet
Countersink Angle: Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Grip Length:
Between 99.0 degrees and 101.0 degrees Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-I-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.970 inches and 1.031 inches
Special Features: Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Countersink Angle:
Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88, lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 99.0 degrees and 101.0 degrees
lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax. Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Special Features:
Material: Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Lubricants listed below may be applied to any or all components if required for performance: dry film lube mos2, dag 250, molykote m-88,
Titanium alloy uns r56400 nut Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	lauric acid, wwm-carbo wax, cetyl alcohol, everlube 812 per mil-l-81329 or paraffin wax.
Surface Treatment: Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Passivate sleeve Shelf Life: N/a Unit Of Measure: Demilitarization:	Titanium alloy uns r56400 nut
Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment:
N/a Unit Of Measure: Demilitarization:	Passivate sleeve
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
	
No.	Demilitarization:
140	No

Fiig:

A040a0