

View Online at <https://aerobasegroup.com/nsn/5320-01-542-9866>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.097 inches and 3.117 inches

**Head Style:**

Straight pan

**Head Height:**

Between 0.078 inches and 0.088 inches

**Width Between Flats:**

Between 0.158 inches and 0.161 inches

**Shank Diameter:**

Between 0.374 inches and 0.375 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

C-17a aircraft

**Grip Length:**

Between 2.557 inches and 2.567 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Shear Strength:**

95000 single pounds per square inch

**Product Name:**

Pin-riquet

**Material:**

Steel comp 4140 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

305 cage 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-5626 spec.