# NSN 5320-01-542-9866

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-542-9866



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 3.097 inches and 3.117 inches

### Head Style:

Straight pan

#### **Head Height:**

Between 0.078 inches and 0.088 inches

#### Width Between Flats:

Between 0.158 inches and 0.161 inches

#### Shank Diameter:

Between 0.374 inches and 0.375 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# End Application:

C-17a aircraft

Grip Length:

Between 2.557 inches and 2.567 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

## Shear Strength:

95000 single pounds per square inch

#### Product Name:

Pin-rivet

#### Material:

Steel comp 4140 or steel comp 8740

#### **Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

305 cage 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# NSN 5320-01-542-9866

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

# Mil-std (military Standard):

Mil-s-5626 spec.

