

View Online at <https://aerobasegroup.com/nsn/5320-01-542-9867>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.072 inches and 1.092 inches

Head Style:

Straight pan

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.094 inches and 0.096 inches

Shank Diameter:

Between 0.248 inches and 0.249 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-17a aircraft

Grip Length:

Between 0.682 inches and 0.692 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Product Name:

Pin-riquet

Material:

Steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

305 cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.