

View Online at <https://aerobasegroup.com/nsn/5320-01-543-2647>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.617 inches and 0.637 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.005 inches and 0.010 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.202 inches and 0.203 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.296 inches and 0.301 inches

Countersink Height:

Between 0.039 inches and 0.041 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-17a aircraft

Grip Length:

Between 0.182 inches and 0.192 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet

Special Features:

0.155 wide groove between grip and threads

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258 cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A528u0