
## NSN 5320-01-543-9881

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.513 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

0.080 inches

#### Shank Diameter:

Between 0.2177 inches and 0.2182 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.300 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

C-17a aircraft

#### Grip Length:

0.188 inches

## Thread Size:

0.183 inches

#### Shear Strength:

85000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Pin-rivet

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams5731 mfr ref single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Hi-shear no. 358 mfr ref single treatment response

## Thread Series Designator:

Unjf

#### Shelf Life:

N/a

# NSN 5320-01-543-9881

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

