

View Online at <https://aerobasegroup.com/nsn/5320-01-544-1264>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.875 inches

**Head Style:**

Flush countersunk

**Head Height:**

Between 0.010 inches and 0.015 inches

**Width Between Flats:**

Between 0.160 inches and 0.180 inches

**Shank Diameter:**

Between 0.3115 inches and 0.3120 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.557 inches and 0.562 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17a aircraft

**Grip Length:**

0.500 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.3125 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin-rivet

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Per hi-shear specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0