## NSN 5320-01-544-7039

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-544-7039 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.588 inches and 0.608 inches **Head Style:** Flush countersunk Width Between Flats: 0.100 inches **Shank Diameter:** Between 0.1621 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.311 inches Lubrication: Cetyl alcohol **End Application:** Rq-4a **Grip Length:** Between 0.307 inches and 0.317 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** Between 99.5 degrees and 101.5 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** +5103 mfr ref single treatment response **Thread Series Designator:** Unjc

N/a

Shelf Life:

## NSN 5320-01-544-7039

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0