# NSN 5320-01-544-7495

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.758 inches and 0.778 inches

# Head Style:

Straight pan

## **Head Height:**

Between 0.077 inches and 0.090 inches

## Width Between Flats:

Between 0.104 inches and 0.119 inches

### Shank Diameter:

Between 0.2016 inches and 0.2036 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.357 inches and 0.377 inches

Lubrication:

Solid film

**End Application:** 

Rq-4a

Grip Length:

Between 0.433 inches and 0.443 inches

## Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

# Thread Size:

0.190 inches

## Shear Strength:

6130 double pounds per square inch

### Material:

Iron alloy 660

### Material Specification:

Ams5737 assn standard single material response or ams5731 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-544-7495

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

