NSN 5320-01-545-0761

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-545-0761 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.073 inches and 1.093 inches **Head Style:** Straight pan **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.285 inches and 0.295 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Rq-4a **Grip Length:** Between 0.683 inches and 0.693 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.250 inches Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum alloy **Surface Treatment Specification:** Per hi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-545-0761

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0