

View Online at <https://aerobasegroup.com/nsn/5320-01-545-6068>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.312 inches and 1.332 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.189 inches and 0.193 inches

**Shank Diameter:**

Between 0.436 inches and 0.437 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.614 inches and 0.624 inches

**Lubrication:**

Solid film or dry film

**Grip Length:**

Between 0.745 inches and 0.755 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.437 inches

**Countersink Angle:**

100.0 degrees

**Product Name:**

Pin, -riquet, threaded, shear, 100deg. C'sunk head, hex point drive

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0