

View Online at <https://aerobasegroup.com/nsn/5320-01-546-0075>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.920 inches and 0.940 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

0.112 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.226 inches

**End Application:**

F-22 raptor

**Grip Length:**

Between 0.620 inches and 0.630 inches

**Thread Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

5380 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

"s" indicates spline lock recess

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4928 assn standard single material response

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Ams2486 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A528u0