

View Online at <https://aerobasegroup.com/nsn/5320-01-546-1545>

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 15.8 millimeters and 17.3 millimeters

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 1.9 millimeters and 2.3 millimeters

**Shank Diameter:**

Between 3.8 millimeters and 3.9 millimeters

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 6.8 millimeters and 6.9 millimeters

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

9.0 millimeters

**Thread Size:**

4.0 millimeters

**Thread Pitch In Millimeters:**

0.70

**Countersink Angle:**

100.0 degrees

**Thread Tolerance Class:**

4h external

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4962 assn standard single material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-shear 294 mfr ref single treatment response

**Thread Series Designator:**

Iso m

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0