

View Online at <https://aerobasegroup.com/nsn/5320-01-546-8592>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.660 inches and 1.680 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.160 inches and 0.180 inches

Shank Diameter:

Between 0.327 inches and 0.328 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.489 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-5 aircraft

Grip Length:

Between 1.120 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

108000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.