# NSN 5320-01-547-2316

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-547-2316



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.385 inches and 2.405 inches

# Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.122 inches and 0.142 inches

# Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### **End Application:**

C-5 aircraft

# Grip Length:

Between 1.995 inches and 2.005 inches

# Thread Size:

0.250 inches

# Shear Strength:

9300 double pounds per square inch

# **Countersink Angle:**

100.0 degrees

# Material:

Titanium alloy uns r56400

# **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

# **Thread Series Designator:**

Unjf

#### **Specification Data:**

73197-hl11 manufacturers standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-547-2316

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

