NSN 5320-01-547-2316



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-547-2316 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.385 inches and 2.405 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.122 inches and 0.142 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** C-5 aircraft **Grip Length:** Between 1.995 inches and 2.005 inches **Thread Size:** 0.250 inches **Shear Strength:** 9300 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 73197-hl11 manufacturers standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-547-2316

Pin-rivet - Page 2 of 2



Fiig:

A528u0