

View Online at <https://aerobasegroup.com/nsn/5320-01-547-4873>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.770 inches and 0.790 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.162 inches and 0.163 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.331 inches and 0.339 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.495 inches and 0.505 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Countersink Angle:

130.0 degrees

Special Features:

Identify with color orange on thread end

Material:

Titanium alloy

Material Specification:

6al-4v per ams 4928 or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi kote 1, specification 294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0